

## Voltage tester



### GT-11

Contactless voltage tester (50-1000 V)

- To determine voltage at outlets, light fixtures, power switches, wires and cables or for location of wire breaks.

#### Characteristics

- Fast, easy, contactless voltage testing
- Clear LED and acoustic warning signal when the voltage has been determined
- ON/OFF switch provides longer battery service life
- Handy pen format, which fits easily into a jacket or tool pocket
- Fast, easy replacement of batteries

Technical Data	
Voltage range:	AC V 50-1000
Frequency:	50-500 Hz
Measuring category:	CAT IV, 1,000 V

Item	Part No.	
GT-11 Contactless voltage tester (50-1000 V)	<b>50090224</b>	
Scope of supply	Part No.	Page
Batteries 2 x 1.5 V		



### GT-55E

Bipolar voltage tester with LED display

#### Characteristics

- Display of AC and DC voltage
- Bipolar rotary field testing
- Unipolar phase testing, optical and acoustic
- Continuity check, optical and acoustic
- Diode test
- Polarity display, loud beeper
- Unique measuring point illumination for working in poor lighting conditions
- IP64 - splash water proof and dust tight

Technical Data	
Voltage range:	6 - 690 V AC/DC
Frequency:	0 - 65 Hz
Measuring category:	CAT III, 1000 V; CAT IV, 600 V

Item	Part No.	
GT-55E bipolar voltage tester with LED display	<b>52021955</b>	
Scope of supply	Part No.	Page
Batteries 2 x 1.5 V		

Accessories	Description	Part No.	Page
TC-30	Nylon carry bag with belt loop	50075365	663
	Replacement tips	52034234	

**GT-85E**

Bipolar voltage tester with LCD display

- Backlit LCD
- True resistance measurement up to 2000 ohms
- Bipolar rotary field testing

**Characteristics**

- Display of AC and DC voltage
- Unipolar phase testing, optical and acoustic
- Continuity check, optical and acoustic
- Diode test
- Polarity display, loud beeper
- Unique measuring point illumination for working in poor lighting conditions
- IP64 - splash water proof and dust tight

Technical Data	
Voltage range:	6 - 690 V AC/DC
Resistance:	0 - 2000 Ω
Frequency:	0 - 65 Hz
Measuring category:	CAT III, 1000 V; CAT IV, 600 V

Item	Part No.	
GT-85E bipolar voltage tester with LCD display	<b>52021956</b>	
Scope of supply	Part No.	Page
Batteries 2 x 1.5 V		

Accessories	Description	Part No.	Page
TC-30	Nylon carry bag with belt loop	50075365	663
	Replacement tips	52034234	



Voltage tester



**GT-65E**

Voltage tester with LED display

- Self-test
- Data storage function is automatically activated for 10 seconds when the tester is removed from the voltage being measured

**Characteristics**

- AC/DC voltage and polarity measurement
- Warning when voltage of 1000 V AC / 1000 V DC is reached
- Continuity check and phase determination
- Safe contactless voltage testing
- Optical and acoustic continuity check

Technical Data	
Voltage range:	8 - 1000 V AC, 6 - 1000 V DC
Continuity test:	0 - 50 kΩ
Frequency:	45 - 65 Hz
Measuring category:	CAT III, 1000 V; CAT IV, 600 V

Item	Part No.		
GT-65E Voltage tester with LED display	<b>50121677</b>		
Scope of supply	Description	Part No.	Page
TSG-4	Test leads	52022554	618
	Batteries 2 x 1.5 V		

Accessories	Part No.	Page
TC-30	Nylon carry bag with belt loop	50075365 / 663



**TSG-4**

Test leads

**Suitable for:**

- GT-65E and GT-95E

Item	Part No.
Test leads	<b>52022554</b>

**GT-95E**

Voltage tester with LCD display

- **LCD and two-colour LEDs**
- **Selectable SHAKER function. The device starts to vibrate from voltages of 15 V AC upwards**
- **RCD function (FI circuit breaker test)**

**Characteristics**

- AC/DC voltage and polarity measurement
- Warning when voltage of 1000 V AC / 1000 V DC is reached
- Data storage function is automatically activated for 10 seconds when the tester is removed from the voltage being measured
- Continuity check and phase determination
- Safe contactless voltage detection
- Optical and acoustic continuity check
- Self-test



Technical Data	
Voltage range:	8 - 1000 V AC, 6 - 1000 V DC
Continuity test:	0 - 50 kΩ
Frequency:	45 - 65 Hz
RCD:	30 mA at 230 V
Measuring category:	CAT III, 1000 V; CAT IV, 600 V

Item	Part No.		
GT-95E Voltage tester with LCD display	<b>50121685</b>		
Scope of supply	Description	Part No.	Page
TSG-4	Test leads	52022554	618
	Batteries 2 x 1.5 V		

Accessories	Description	Part No.	Page
TC-30	Nylon carry bag with belt loop	50075365	663

